

BLUETTI AC2P PORTABLE POWER STATION

GENERAL

Weight: About 3,6kg / 7,9lbs

Dimensions (L x W x D): 250 × 156,5 × 174,5mm / 9,8 × 6,16 × 6,87in

Charging Temperature: 0°C-40°C / 32°F-104°F

Discharging Temperature: -20°C-40°C / -4°F-104°F

Storage Temperature: -20°C-c to 40e49Fto1069F

Certifications: UL Standard, CEC, DOE, FCC, CA Prop 65

Warranty: 5 Years

BATTERY INFO

Capacity: 230,4Wh / 9Ah

Type: LiFePO4 (Lithium Iron Phosphate)

Life Cycles: 3.000+ Cycles to 80% Original Capacity

Shelf-life: Recharge to 80% Every 3-6 Months

Management System: MPPT Controller, BMS, etc..

OUTPUT

AC Outlets: 1×230V/1,3A; 300W In Total

Inverter Type: Pure Sine Wave

Surge Power: 600W

USB-C: 1 ×100W Max. .

USB-A: 2 ×5VDC/2,4A 12W (Each Port)

12V DC Outlets: 1 ×12V/10A (Car outlet, regulated.)

INPUT

AC Power Input (Turbo Mode): 270W Max.

Solar Input: 200W Max, 12V-28VDC, 8,2A

Car Input: 12/24V from Cigarette Lighter Port

Max Input: 270W

RECHARGE TIMES

AC Charging Cable

(270W Turbo Charging): ≈1,2 Hours

Solar Panel (s)(200W): ≈1,5 Hours (With prime sunshine, ideal orientation, and low temperature)



GRIDX
metering and control