

DELTA PRO 3 PORTABLE POWER STATION

AC OUTPUT

Max Continuous Output:

4000W Max

Surge Output:

8000W, 400ms

Output Voltage:

230V

X-Boost:

6000W, Max

X-Fusion:

Yes, 230V/2900W AC input, 4000W

Max AC output

X-Stream:

Yes

EPS/UPS:

<10ms, UPS

AC Power IN/OUT Port (Discharge Only):

230V~17.4A 50Hz

AC Outlets:

4× Type F, 230V/16A; 1× CEE 16A,
230V/16A

DC OUTPUT

USB-C:

USB-C*2, 5/9/12/15/20V 5A 100W
Max

USB-A-Fast:

USB-A*2, 5V 2.4A 9V 2A 12V 1.5A
18W Max

Car Power Output:

No

12V DC Output:

12.6V/30A 378W Total; DC5521,
1X, 5A Max; Anderson, 1X, 30A
Max

Remote Control Port:

1X



Colour:

Silver

Capacity:

4096Wh

1 Unit Capacity Extend:

12kWh

Max Extend Range:

12kWh

Dimension (L×W×H):

Approx. 693mm × 341mm × 410mm

Net Weight (KG):

Approx. 51.5kg (113.54 lb)

DELTA PRO 3 PORTABLE POWER STATION

INPUT

Utility Power Charging:

C20 port, 220–240V 12.5A 50/60Hz 2900W Max

Bypass Mode: 220–240V 12.5A 50/60Hz

Adjustable AC Charging Speed:

Yes

EV Charger Charging (AC Power IN/OUT Port):

AC Power IN/OUT Port

4000W Max, 220–240V 20A 50/60Hz

Solar Input:

2600W, Max, 2 Ports,

HPV: 30–150V/15A, 1600W Max

LPV: 11–60V/20A, 1000W Max

Car Input:

12V 8A Max, 48V 20A Max

Generator Input:

3200W, Max (with Smart generator 4000)

0–80% Charge Time:

50 min (1C Charging)

Bond Charge Input (with 1*EB):

7000W, Max

BATTERY

Extra Battery Port:

2X, Support DP EB, DP3 EB

Life Cycle:

4000cyc, 80%

CTC Craftsmanship:

yes

Battery Material:

LFP

IP rate for Battery Pack:

IP65

