

RIVER 3 PLUS PORTABLE POWER STATION

DIMENSIONS

Capacity: 286Wh/89600mAh

Dimension:

234 x 231 x 146 mm

9.2 x 9.1 x 5.8 inches

Net. Weight: 4.7 kg/10.4 lb

Battery Chemistry: LFP (LiFePO4)

Cycle Life: 3000 cycles to 80% capacity

OUTPUT

AC Output:

3 × 230V~50Hz, 600W Max

(Surge 1200W, X-Boost 1200W)

USB-A Output:

2 × 5V=2.4A, 12W Per Port, Total 24W

USB-C Output:

1 port, 5/9/12/15V=3A Max, 20V=5A Max, 100W Max

Car Output:

1 port, 12.6V, 10A, 126W

Wireless: No

INPUT

AC Recharge:

200~240V, 3A Max, 50/60Hz, 360W

0-100% in 60 min

Solar Recharge:

11~55V, 13A Max, 220W,

0-100% in 1.5 hr

(45W input 0-100% in 7.3 hrs)

(60W input 0-100% in 5.5 hrs)

(110W input 0-100% in 3 hrs)

Car Recharge:

11-55V, 8A Max, 220W Max

0-100% in 3.3 Hr

Generator Recharge:

200-240V, 3A Max, 50/60Hz, 360W

0-100% in 60 min



OTHERS

UPS: <10ms

EB: Only support 1 extra battery, 2 models to choose: EB300 (286Wh); EB600 (572Wh)

APP: Wi-Fi & Bluetooth

Noise: 30db

Waterproof: IP54 only for battery pack, not the whole package

Warranty: 5 Years

ENVIRONMENT TEMPERATURE

Optimal Operating Temperature:

20°C-30°C (68°F-86°F)

Charge Temperature:

0°C-45°C (32°F-113°F)

Discharge Temperature:

-10°C-45°C (14°F-113°F)

Storage Temperature:

20°C-30°C (68°F-86°F)

GRIDX
www.gridx.rs